



Certified to:  
 ANSI STD Z83. 11-2016  
 CSA STD 1.8-2016  
 NSF/ANSI Std.4



**NFF4L / NFF4N**

### FEATURES & BENEFITS

- **Heavy duty stainless steel:** Front, top ledge, and door offer a sleek, premium look, while galvanized steel sides and back ensure durable, cost-efficient construction.
- **Welded 1.5 mm (16-gauge) stainless steel fry pot:** Offers lasting durability, generous 21.3–25 L (45-50 lb) capacity and embossed oil level markings for easy monitoring
- **Efficient heating system:** Powerful burners with high-heat baffles in each heat exchange tube maximize thermal transfer for faster, consistent performance
- **120,000 BTU:** High-output cooking power engineered to meet the demands of fast-paced commercial kitchens
- **Adjustable thermostat:** Precise control from 93 °C to 204 °C (200 °F to 400 °F), ensuring optimal results across a wide range of foods
- **Automatic shutoff:** Activates at 232 °C (450 °F), protecting both the unit and your kitchen with this built-in safety feature
- **Advanced gas control valve:** Blocks gas flow until the pilot is lit and automatically shuts it off if the flame goes out for added safety
- **Standing pilot design:** Enables instant ignition, getting the fryer up and running fast for efficient kitchen operation
- **Integrated 1.25" front-access drain with extension:** Streamline cleaning, filtering, and oil replacement

### GAS

NFF4L: Liquid Propane Gas

NFF4N: Natural Gas

¾" gas connection

### WARRANTY

2 years parts & labour

5 year fry tank (parts-only)

# NORIOTA

## GAS FLOOR FRYER – 4 TUBE – 45 – 50 LB

### Technical Data

<b>BTU</b>	120,000 Total 30,000 per burner
<b>Oil Capacity</b>	21.3– 25 L 45 – 50 lb
<b>Fry Pot Dimensions (W x D)</b>	35.5 x 35.2 cm 14 x 13.85 in
<b>Working Height</b>	87CM / 34.3 in
<b>Fry Baskets</b>	2, nickel plated
<b>Thermostat Range</b>	93 °C to 204 °C (200 °F to 400 °F)
<b>Automatic Shutoff</b>	Yes, at 232 °C (450 °F)
<b>Control Type</b>	Millivolt
<b>Ignition Type</b>	Standing pilot
<b>Gas Connection Size</b>	3/4"
<b>Legs</b>	15 cm (6 in) Adjustable
<b>Drain</b>	3.175 cm (1.25 in) Diameter- Front access with extension pipe
<b>Dimensions</b>	
<b>Unit Dimensions</b>	39.5 x 76.5 x 116.2 cm 15.57 x 30.12 x 45.75 in
<b>Unit Weight</b>	74 kg (163 lb)
<b>Shipping Dimensions</b>	46 x 83 x 87 cm 18.11 x 32.68 x 34.25 in
<b>Shipping Weight</b>	82 kg (180 lb)
<b>Includes</b>	
(2) nickel plated oblong wire mesh baskets, (1) nickel plated tube rack, (1) drain extension pipe, (4) adjustable legs	

