

NORIOTA

ENERGY STAR GAS FLOOR FRYER – 4 TUBE – 45 – 50 LB



Intertek

Certified to:
ANSI STD Z83. 11-2016
CSA STD 1.8-2016
NSF/ANSI Std.4



NFF4LES / NFF4NES

FEATURES & BENEFITS

- **Energy efficient design:** 84,000 BTU delivers optimized cooking power while saving energy with ENERGY STAR registered models
- **Heavy duty stainless steel:** Front, top ledge, and door offer a sleek, premium look, while galvanized steel sides and back ensure durable, cost-efficient construction
- **Welded 1.5mm (16-gauge) stainless steel fry pot:** Offers lasting durability, generous 21.3–25 L (45-50 lb) capacity and embossed oil level markings for easy monitoring
- **Efficient heating system:** Powerful burners with high-heat baffles in each heat exchange tube maximize thermal transfer for faster, consistent performance
- **Adjustable thermostat:** Precise control from 93 °C to 204 °C (200 °F to 400 °F), ensuring optimal results across a wide range of foods
- **Automatic shutoff:** Activates at 232 °C (450 °F), protecting both the unit and your kitchen with this built-in safety feature
- **Advanced gas control valve:** Blocks gas flow until the pilot is lit and automatically shuts it off if the flame goes out for added safety
- **Standing pilot design:** Enables instant ignition, getting the fryer up and running fast for efficient kitchen operation
- **Integrated 1.25" front-access drain with extension:** Streamline cleaning, filtering, and oil replacement

GAS

NFF4LES: Liquid Propane Gas

NFF4NES: Natural Gas

$\frac{3}{4}$ " gas connection

WARRANTY

2 years parts & labour

5 year fry tank (parts-only)

NORIOTA Ltd

www.noriota.ca | support@noriota.ca | 1-877-NORIOTA

November 2025

NORIOTA

ENERGY STAR GAS FLOOR FRYER – 4 TUBE – 45 – 50 LB

Technical Data

BTU	84,000
Oil Capacity	21.3 – 25 L 45 – 50 lb
Fry Pot Dimensions (W x D)	35.5 x 35.2 cm 14 x 13.85 in
Working Height	88.4 cm (34.8 in)
Fry Baskets	2, nickel plated
Thermostat Range	93 °C to 204 °C (200 °F to 400 °F)
Automatic Shutoff	Yes, at 232 °C (450 °F)
Control Type	Millivolt
Ignition Type	Standing pilot
Gas Connection Size	3/4"
Legs	15 cm (6 in) Adjustable
Drain	3.175 cm (1.25 in) Diameter- Front access with extension pipe

Dimensions

Unit Dimensions	39.4 x 76.2 x 124.3 cm 15.5 x 30 x 48.94 in
Unit Weight	74 kg (163 lb)
Shipping Dimensions	46 x 83 x 87 cm 18.11 x 32.68 x 34.25 in
Shipping Weight	82 kg (180 lb)

Includes

(2) nickel plated oblong wire mesh baskets, (1) nickel plated tube rack, (1) drain extension pipe, (4) adjustable legs

