

NORIOTA

320LB SELF-CONTAINED ICE MAKER



FULL DICE CUBE
2.2 x 2.2 x 2.2 CM
7/8 x 7/8 x 7/8 IN

*Available in half dice upon request



NI320F



Advanced Controller with Auto Clean and Diagnostics



Removeable and Cleanable Air Filter to Protect Condenser



Convenient Ice Scoop with Built-In Scoop Holder



Heavy Duty Nickel Plated Evaporator

FEATURES & BENEFITS

- **Large ice production and extra storage capacity:** produces up to 148K kg (328 lb) per day and stores 58 kg (127 lb) of clear ice in its integrated ice bin
- **Clear ice with less impurities:** Vertical evaporator with water flow design uses gravity to remove impurities during the freezing process, producing clear and great tasting ice
- **Advanced digital programmable control system:** Easy to use with precise control over settings and feedback on the status of the machine
- **Automatic self-cleaning function for use with nickel-safe cleaning solution:** Ensures hygiene and reduces maintenance effort, safe for all components
- **Automatic shut-off and overflow protection:** Experience worry-free operation with this standard feature
- **15.24 cm (6 in) adjustable leveling legs:** Allow for easy leveling on uneven surfaces, ensuring stability and optimal performance while also making it easy to clean under the machine

ELECTRICAL

115V / 60Hz / 1Ph / 8A-9A
190 cm (74.4 in) cord set included



NEMA 5-15P

WARRANTY

5-year compressor (parts only)
2-year parts & labour

NORIOTA Ltd

www.noriota.ca | support@noriota.ca | 1-877-NORIOTA

August 2025

NORIOTA

NI320F 320LB SELF-CONTAINED ICE MAKER

Technical Data

Daily Ice Production	
Air Temperature 21°C (70°F) / Water Temperature 10°C (50°F)	148 kg (328 lb)
Air Temperature 32°C (90°F) / Water Temperature 21°C (70°F)	111 kg (244 lb)
Storage Bin Capacity	58 kg (127 lb)
Refrigerant	R290

Installation

- REQUIRED: Gravity drain connection & water supply line
- RECOMMENDED: Water Filter
- 5CM (2IN) clearance from the wall in rear to ensure proper cooling air circulation; no clearance required on sides

Operating Requirements

Ambient Temperature Range	4.4 °C to 43 °C (40 °F to 110 °F)
Water Temperature Range	4.4 °C to 32 °C (40 °F to 90 °F)
Water Supply Line Connection	3/8" FPT
Water Pressure Range	Min 20 PSI Max 80 PSI (Above 80 requires a regulator) Min 1.4 Bar Max 5.5 Bar
Water Usage / 45.5 kg (100 lb) of Ice Produced	50 L (13.3 Gallons)
Energy Usage / 45.5 kg (100 lb) of Ice Produced	6.48 kWh

Dimensions

Unit Dimensions	76.2 x 71.1 x 98.6 cm (30x 28 x 39 in)
Unit Weight	67 kg (147.7 lb)
Shipping Weight	75 kg (165.3 lb)
Shipping Dimensions	81.7 x 77.1 x 88.5 cm (32 x 30 x 35 in)

Includes

- Ice Scoop
- Tubing for supply and drain lines
- NEMA 5-15 cord set

