

NORIOTA



Certified to
ANSI UL 563



Certified to
ANSI-NSF 12



FULL DICE CUBE

2.2 x 2.2 x 2.2 cm
7/8 x 7/8 x 7/8 in

*Available in half dice
upon request



NI370F



NI370F Shown on
NIB580 Bin, Sold
Separately



Advanced Controller
with Auto Clean and
Diagnostics



Heavy Duty Nickel
Plated Evaporator


370LB MODULAR ICE MAKER – 30IN WIDTH

FEATURES & BENEFITS

- Large ice production in standard 30 inch wide footprint :** This common width design fits on most 30 inch wide ice bins and produces up to 169 kg (373 lb) of clear ice per day
- Clear ice with less impurities:** Vertical evaporator with water flow design uses gravity to remove impurities during the freezing process, producing clear and great tasting ice
- Advanced digital programmable control system:** Easy to use with precise control over settings and feedback on the status of the machine
- Automatic self-cleaning function for use with nickel-safe cleaning solution:** Ensures hygiene and reduces maintenance effort, safe for all components
- Automatic shut-off and overflow protection:** Experience worry-free operation with this standard feature
- Internal LED light in the storage bin:** When combined with the matching ice storage bin NIB580 (sold separately); increase visibility inside the bin, making it easier to monitor ice levels and access ice even in low-light conditions
- Stackable design for expanded ice production needs:** Stack 2 units on top of each other on the same ice bin; provides the flexibility to scale up your ice-making capacity as needed, making it an ideal solution for growing businesses (requires stacking kit sold separately)

ELECTRICAL

115V / 60Hz / 1Ph / 7.5-10.5A
190 cm (74.4 in) cord set included



NEMA 5-15P

WARRANTY

5-year compressor (parts only)
2-year parts & labour

NORIOTA

NI370F 370LB MODULAR ICE MAKER – 30IN WIDTH

Technical Data

Daily Ice Production	
Air Temperature 21°C (70°F) / Water Temperature 10°C (50°F)	169 kg (373 lb)
Air Temperature 32°C (90°F) / Water Temperature 21°C (70°F)	131 kg (288 lb)
Storage Bin Capacity	Must be used with separate ice bin: NIB470 – 213 kg (470 lb) storage NIB580 – 263 kg (580 lb) storage
Refrigerant	R290
Installation	
• REQUIRED: Gravity drain connection & water supply line	
• RECOMMENDED: Water Filter	
• 15 cm (6 in) clearance required on left side and rear, 51 cm (20 in) required on right side for proper cooling air circulation	
Operating Requirements	
Ambient Temperature Range	4.4 °C to 43 °C (40 °F to 110 °F)
Water Temperature Range	4.4 °C to 32 °C (40 °F to 90 °F)
Water Supply Line Connection	3/8" FPT
Water Pressure Range	Min 15 PSI Max 80 PSI (Above 80 requires a regulator) Min 1.0 Bar Max 5.5 Bar
Water Usage / 45.5 kg (100 lb) of Ice Produced	50 L (13.3 Gallons)
Energy Consumptions / 45.5 kg (100 lb) of Ice Produced	5.9 kWh
Dimensions	
Unit Dimensions	76.2 x 61.0 x 53.3 cm (30 x 24 x 21 in)
Unit Weight	49 kg (108 lb)
Shipping Weight	56 kg (137.8 lb)
Shipping Dimensions	82 x 68 x 72.4 cm (32 x 27 x 29 in)
Includes	
• Ice Scoop	
• Tubing for supply and drain lines	
• NEMA 5-15 cord set	

