

NORIOTA

GAS RANGE / GRIDDLE COMBO – 60IN WIDTH



Intertek

Certified to:
ANSI STD Z83. 11-2016
CSA STD 1.8-2016
NSF/ANSI Std.4



NR60G24

FEATURES & BENEFITS

- **Durable Construction:** Built with heavy-duty stainless steel for the front, back inner shell, and support legs
- **Flexible Gas Compatibility:** Pre-configured for natural gas use, but easily convertible to liquid propane with included parts ideal for field adaptability

OVEN FEATURES

- **Powerful Heating:** 30,000 BTU total output ensures fast and consistent cooking
- **Precision Control:** Adjustable thermostat from 65.5 °C to 288 °C (150 °F to 550 °F) gives you flexibility for everything from slow roasting to high-temp baking
- **Safety First:** Flame failure safety device prevent gas leaks if the flame goes out
- **Durable Build:** Steel sides and porcelain oven liner offer longevity and easy cleaning
- **User-Friendly Design:** Spring-loaded door for smooth operation, cool-touch stainless steel handle for safety, removable crumb tray & two adjustable/removable racks for versatile cooking setups. Fits full size sheet pans

TOP BURNERS FEATURES

- **High Output:** Each burner delivers 30,000 BTU; ideal for rapid boiling or searing
- **Easy Maintenance:** Removable 12 in x 12 in cast iron grates simplify cleaning
- **Quick Ignition:** Individual standing pilots and control knobs allow instant startup and precise flame control

GRIDDLE FEATURES

- **Polished Steel Cooling Surface:** 1.9 cm (3/4 in) polished steel plate; 24 in x 14 in surface
- **Fully Welded Side & Back Plates:** 7.6 cm (3 in) high for durability and strength
- **Removable Drip Trays**

GAS

NR60G24: Natural Gas Field convertible to Liquid Propane with included components $\frac{3}{4}$ " gas connection

WARRANTY

2-year parts & labour

NORIOTA

GAS RANGE / GRIDDLE COMBO – 60IN WIDTH

Technical Data.

BTU	280,000 Total Oven - 30,000 x2 Burners - 30,000 each x6 Griddle - 40,000 x1
Burner Grates	30.5 x 30.5 cm (12 x 12 in) Removable Cast Iron
Burner Control	Independent Pilot and Control Knob for Each Burner
Front Ledge	12.7 cm (5 in) Deep, Stainless Steel
Oven Dimensions	68 x 66 x 35.6 cm 26.75 x 26 x 14 in
Fits Full Size Sheet Pans?	Yes
Oven Thermostat Range	121 °C – 288 °C (250 °F - 550°F)
Oven Door	Stainless Steel, Spring Loaded Close, Cool Touch SS Handle
Oven Liner	Steel Sides, Porcelain Bottom
Oven Racks	4
Back Riser	62.9 cm (24.75 in) H
Legs	15 cm (6 in) Adjustable Stainless Steel
Griddle Specs (W x D)	1.9 cm (0.75 in) Thick Polished Steel Plate, 61 x 53.3 cm (24 x 21 in) Cooking Surface, 3 in Welded Side and Backsplash

Dimensions

Unit Dimensions (W x D x H)	152.4 x 83 x 153.2 cm 60 x 32.67 x 60.33 in
Unit Weight	312 kg (687.8 lb)
Shipping Dimensions (W x D x H)	165 x 101 x 105 cm 65 x 39.8 x 41.34 in
Shipping Weight	362 kg (798.1 lb)

Includes

(1) stainless back riser, (2) oven racks per oven, (1) crumb tray per oven, (4) adjustable legs, (1) gas conversion kit

