

NORIOTA

BUILT IN SERIES – Zero Clearance Design
Stainless Steel Door Easily Converts to Overlay Panel Ready



GOURMET CUBE
3.2 x 3.2 x 3.2 CM
1.25 x 1.25 x 1.25 IN



Showu with custom wood overlay panel (not included)

NUI15GOPSS

Cabinet

Cabinet Finish	Stainless steel
Door Style	Swing, right hinged (field reversible to left hinged)
Door Panel	Stainless steel, can be removed for installation of custom 19 mm (3/4 in) wood panel
Handle	1.9 cm (3/4 in) Diameter stainless steel
Hinge	Stainless steel with built-in door close assist to ensure door closure
Maximum Door Opening	135°, door and handle will not hit adjacent cabinetry
Interior Color	White
Interior Light	3 Colour LED : white / blue / amber
Door Gasket	Black, magnetic and replaceable

Electrical Data

Electrical Requirements	115V/60Hz / 1Ph / 15A
Voltage Range	104V – 127V
Rated Current Ice Making / Harvest	3.3A/2.1A
Power Cord Length	180 cm (72 in)
Plug Type	NEMA5-15P

Warranty

5-year compressor (parts only), 1-year parts & labour

FEATURES & BENEFITS

- Door is Both Stainless Steel or Overlay Panel Ready:** Allows for custom 1.9 cm (3/4 in) panel overlays, giving you the flexibility to match your cabinetry or use the included stainless steel door
- Rated for Outdoor Use:** Upgraded components and full stainless steel exterior that looks great with exceptional performance both indoors and outdoors
- Zero-Clearance Design:** Achieves seamless, flush integration into any built-in setting, ensuring a clean, custom look
- Premium Gourmet Clear Ice:** Produces up to 29.5 kg (65 lb) per day of crystal clear extra large octagon shaped ice cubes, ice contains almost no impurities and is slow melting, making it perfect for an elevated drinking experience
- Advanced Controller and Internal LED:** Actively manages the ice making process, sends alerts for cleaning and filter replacement, switch between 3 colors of lighting
- Integrated Water Filter:** Removes impurities and improves taste, easy to replace

INDOOR / OUTDOOR GOURMET ICE MAKER- 15 IN

N
O
R
I
O
T
A

Technical Data

Max. Ice Production - Air Temperature 21°C (70°F) / Water Temperature 10°C (50°F)	29.5 kg (65 lb) Per Day
Ice Storage Capacity	12 kg (26 lb) in Insulated Bin
Controls	Advanced diagnostic digital LED controller with auto clean and alert functions
Sabbath Mode	Yes
Refrigerant	R290

Operating Requirements

Energy Usage Per 45.5Kg (100Lb) of Ice Produced	9.25 kWh
Water Usage Per 45.5Kg (100Lb) of Ice Produced	47.7 L (12.6 Gallons)
Ambient Temp. Operating Range	10°C to 38°C (50°F to 100°F)
Water Temp. Operating Range	4.4°C to 32°C (40°F to 90°F)
Water Pressure Operating Range	20 – 80 PSI (0.138MPa - 0.55MPa) (Above 80 requires a regulator)

Installation

Installation type	Built-in or freestanding
Anti-tip Bracket	Not required
Built-In Installation Type	Inset, frameless - Overlay and framed cabinet styles
Ventilation	Front breathing - No additional clearance required around the sides, minimal clearance required in rear
Water Inlet Connection	1/4" Compression fitting
Drain Connection	Required
Factory Installed Drain Pump	Yes
Integrated Water Filter	Yes, replace from front

Dimensions

Unit Dimensions (Including Feet and Hinge)	37.8 x 62.1 x 85.5-88 cm (14.9 x 24.5 x 33.6-34.6 in)
Net Weight	41.5 kg (91.3 lb)
Toe Kick Height	7.6 cm (3 in)
Adjustable Leveling Feet	1.6-4.2 cm (0.6-1.7 in)
Shipping Dimensions	46.1 x 71 x 96.5 cm (18.1 x 28 x 38 in)
Shipping Weight	47 kg (103 lb)
Cut-Out Dimensions	38.1 x 61 x 85.5-88 cm (15 x 24 x 33.7-34.7 in)

Accessories Included

Ice scoop with holder, drain hose 152.4 cm (60 in)

